



# Single Door Magnetic Lock

MODEL: C280 LED TIMER



## Key Specifications/Special Features:

Product Parameter	Parameter Description
Function:	Fail safe, LED Indicator, Feedback signal, Timer-Delay
Size	250L x 48.5W x25H (mm)
Armature Plate Dimension	180L x 38W x 11H (mm)
Holding Force	280kg(600Lbs)
Input Voltage	12 or 24VDC or 12&24 V Double power
Current	12V/500mA or 24V/250mA
Suitable	Wooden door , Glass door ,Metal door , Fireproof door
Surface Temp	≤+20°C
Operating Temp	-10~+55 (14-131F)
Humidity	0~90%(non-condensing)
Cover Finish	Anodized aluminum
Lock Finish	Zinc
Armature Plate Finish	Zinc

### Advantage :

Collinear Load Test 280kg,600pounds.  
Dual Voltage 12 or 24 VDC(optional).  
The Standard Voltage is 12VDC when Finished.  
MOV Provides Reverse Current Protection.

Anti-Residual Magnetism Designed.  
High Strength Material,Anodized Aluminum Housing.  
Design without Mechanical Failure.  
Increase the holding Force,Dual Insulative Housing.

### OPTIONAL:

ZL Bracket , L Bracket , U Bracket