

UPS 2 KVA INTERACTIVE DISPLAY

AX-2000

MODEL

Capacity

2000 VA | 1200 W

INPUT

Voltage

100V | 110V | 120V: 80 ~ 150 Vac; 220V | 230V | 240V: 162 ~ 295 Vac → (220V: 145 ~ 295 Vac optional)

Frequency

50 / 60 Hz ± 10% (auto-sense)

OUTPUT

Voltage

100 V | 110 V | 120 Vac ± 10% or 220 V | 230 V | 240 Vac ± 10%

Frequency

50 / 60 Hz ± 1% (auto-sense)

Waveform

Mains mode | Pure sine wave | Battery mode | Simulated sine wave

Transfer time

Typical 2 ~ 7 ms; Max.10 ms

BATTERIES

DC voltage

24 V

Configuration

12 V / 9.0 Ah × 2

Recharge time

6 ~ 8 h

COMMUNICATIONS

USB / RS232 / SNMP (optional)

Supports Windows® 98 / 2000 / 2003 / XP / Vista / 2008 / 7 / 8 / 10

OTHERS

Protections

Short circuit - battery overcharge – overdischarge – overload - surge

Humidity

20 ~ 90% RH @ 0 ~ 40°C (non-condensing)

Noise level

≤ 45 dB (1 m)

Net / Gross weight (kg)

14.0 / 14.8

Dimensions (W × D × H)

125 × 380 × 225 (mm)

Packaged dimensions (W×D×H)

180 × 450 × 295 (mm)

Quantity / 20 ft

1000 pcs



*All specifications subject to change without notice.

*Custom-made specifications are acceptable.

© 2016 BDN, Inc All Rights Reserved.

Revision Number: 27
Revision Date: 03-09-2018