

TV-SATELLITAL TAPS 2.4GHZ

The bdn Taps are designed to comply with the highest current standards for Analog and Digital TV/SAT technologies. BDN taps are manufactured with a shielded zamak chassis for greater protection from electromagnetic interference, ideal for community TV projects, television networks in hotels, hospitals and shopping centers.

TECH SPECIFICATION

Items	2 way splitter	3 way splitter	4 way splitter	6 way splitter	8 way splitter
Insertion Loss (IN-OUT)	-dB Max				
5-47MHz	4,5	7,5	8,5	10,5	12,5
47-862MHz	4,5	8,0	8,5	11,5	13,0
950-2150MHz	6,0	10,5	10,5	15	16,5
2150-2400MHz	6,0	11	11,5	16,5	17,5
Isolation (TAP-TAP)	-dB Min				
5-47MHz	>18	>19	>20	>22	>22
47-862MHz	>20	>20	>23	>23	>22
950-2150MHz	>18	>20	>18	>20	>20
2150-2400MHz	>18	>20	>15	>20	>20
Return Loss (IN-OUT)	-dB Min				
5-47MHz	15	15	15	15	15
47-862MHz	15	15	15	15	15
950-2150MHz	15	15	15	15	15
2150-2400MHz	15	15	15	15	15
General Information					
Impedance	75 Ohms		24v / 500mA max.		
RFI Shielding	-120 dB				
Intermodulation	-100 dB		22Khz / DiSeqC		
Test Enviroment: Room Temperature: +25°C					